

3D HDMI SWITCH

User Manual

HDMI 2x1 Switcher

(3D Full HD 1080P)

Bring High-Definition to your life!

This is the final edition of high performance HDMI auto Switcher.

This kind of HDMI auto switcher not only has the key-press-switching function, but also has the automatic function.

This kind of HDMI Amplifier auto Switcher routes high definition video (in multiple resolutions up to 1080p) and digital audio from any one of the several sources to display units.

All inputs accommodate the connections of the high definition video sources simultaneously, compatible well with HD-DVD, SKY-STB, PS3, Xbox360 etc. The output sends the high definition audio/video signals to a high definition display.

Features

This HDMI Amplifier Auto Switcher has many features that enable it to perform

3D 1080P HDMI 2x1 SWITCH

in a superior manner. Among those features you will find:

- 1、 Support 12-bit Deep Color, full 1080p
- 2、 Support 3D display device.
- 3、 Support HDCP
- 4、 Multifunctional on switching : automatic or mechanical
- 5、 Supports with HDMI1.3b.
- 6、 High performance up to 2.5Gbps
- 7、 Supports 15Meters HDMI Cable on both ends of the Switcher
- 8、 Maintains high resolution video - beautiful, sharp HDTV resolutions up to 1080p, 1440p graphics and computer resolutions up to 1920 x 1200 are easily achieved.
- 9、 Controlled by Button, no power needed.

TECHNICAL PARAMETER IN DETAIL

Signal Inputs/Output	HDMI
Input Video Signal	0.5-1.0 volts p-p
Input DDC Signal	5 volts p-p (TTL)
Maximum Single Link Range	1920X1200, 1080P
Output Video	HDMI1.3b+HDCP1.0/1.1 DVI1.0
VGA	640x480,800x600,1024x768,1920x1200
DTV/HDTV	480i/576i/480p/576p/720p/1080i/1080P, 3D
HDMI Compliance	HDMI 1.3b
Frequency	Up to225MHz
Vertical Frequency Range	60Hz
Video Amplifier Bandwidth	2.5Gpbs/225MHz

3D 1080P HDMI 2x1 SWITCH

Resolutions(HDTV)	HDMI SWITCH
Interlaced(50&60Hz)	480i,576i,1080i
Progressive(50&60Hz)	480p,576p,720p,1080p
Limited Warranty	1 Year Parts and Labor
Operating Temperature	0°Cto +70°C
Operating Humidity	10% to 85 % RH (no condensation)
Output Cable Length	60CM
Storage Temperature	-10°Cto +80°C
Storage Humidity	5% to 90 % RH (no condensation)
Power Requirement	No power needed
Accessories Adapter	
User Manual	English Version

Note: Specifications are subject to change without notice.

HDMI 2X1 Product Image

